



ACCURATE FELT & GASKET

Material Specification

HTX-900

EnCore® Combined Materials

Description

HTX-900 is a composite gasket structure consisting of graphite-coated, high-temperature facing material chemically and mechanically fused to an expanded steel core. It is intended for exhaust manifold, header, collector, and EGR system gaskets, as well as other industrial sealing applications that require high strength, thermal integrity, and anti-stick performance. It is available in 0.043, 0.048, 0.060, and 0.093 inch gauges in a sheet size of 20 by 63 inches (usable area).

Specification Properties

Property	Value	Method
Caliper, mm(inch)	1.5 (0.060)	ASTM F 104
Density, g/cc(lb/cu.ft)	2.0 (125)	ASTM F 1315
Compressibility, % (at 34.5MPa)	12	ASTM F 36
Recovery, %	50	ASTM F 36
Tensile Strength, MD, MPa(psi)	27.50 (4000)	ASTM F 152
Tensile Strength, AMD, MPa(psi)	15.20 (2200)	ASTM F 152
Fluid Resistance, IRM903 Oil Change in Thickness, %	2	ASTM F 146
Fluid Resistance, Fuel B Change in Thickness, % Change in Weight, %	3 10	ASTM F 146
Binder Type	Fully Cured Nitrile Butadiene	
Color	Dark Grey	

CONTACT

ADDRESS

3239 S. 51ST Ave.
Cicero, IL 60804

PHONE

708-780-9000

EMAIL

sales@afgco.com

WEBSITE

www.afgco.com

ISO CERTIFIED

9001:2015

The information on this data sheet is based on laboratory test data we believe to be accurate, relevant and reliable. Please look upon these values as guides rather than absolutes. Since actual service conditions for a given application may vary substantially from standard laboratory conditions, specific recommendations or warranties relative to a specific end use cannot be made. The buyer is urged to conduct its own investigations and qualification tests to determine suitability for its intended application. Accurate Felt & Gasket Mfg. Co. shall not be liable for any damages arising out of the use of any of its guide specifications.