

ACCURATE FELT & GASKET MFG. COMPANY

3239 S. 51st Avenue
Cicero, IL 60804
Phone: 708-780-9000 Fax: 708-780-9009
www.afgco.com afg@afgco.com

MATERIAL SPECIFICATION

Betaflex 69

Standard/Nonasbestos Gasket Material

Description:

Betaflex 69 is a cellulose fiber material with nitrile butadiene rubber binder. It has excellent tensile strength, crush resistance, and erosion resistance against high volume fluid flow and impingement. It is used primarily in automatic transmission valve body, pump, and accumulator/channel plate applications as well as typical engine sealing applications. It is intended for use in applications with short duration maximum temperatures up to 180°C (350°F).

Typical Properties:

Property	Value	Method
Density, g/cc(lb/cu.ft)	1.00 (62.4)	ASTM F 1315
Compressibility, % (at 6.9MPa)	13	ASTM F 36
Recovery, %	54	ASTM F 36
Tensile Strength, AMD, MPa(psi)	20.7 (3002)	ASTM F 152
Fluid Resistance, IRM903 Oil		ASTM F 146
Change in Thickness, %	2	
Change in Weight, %	26	
Fluid Resistance, Fuel B		ASTM F 146
Change in Thickness, %	6.5	
Change in Weight, %	26	
Fluid Resistance, Distilled Water		ASTM F 146
Change in Thickness, %	26	
Change in Weight, %	26	

Remarks and Related Documents:

Typical values determined by the test methods required for ASTM F-104, Type 3 materials.

EnCore®, Hydro-Fused®, MicroPore®, Pro-Formance®, Select-a-Seal®, Syntheseal®, Thermo-Tork®, and Voltoid® are registered trademarks of Interface Performance Materials, Inc. Select-a-Shield is a trademark of Interface Performance Materials, Inc.

Revised 06/20/17

The information on this data sheet is based on laboratory test data we believe to be accurate, relevant and reliable. Please look upon these values as guides rather than absolutes. Since actual service conditions for a given application may vary substantially from standard laboratory conditions, specific recommendations or warranties relative to a specific end use cannot be made. The buyer is urged to conduct its own investigations and qualification tests to determine suitability for its intended application. Accurate Felt & Gasket Mfg. Co. shall not be liable for any damages arising out of the use of any of its guide specifications.

ISO 9001: 2008 Registered